

Date		Project	
Type		Part Number	

PRIME R ALL-IN-ONE PERFORMANCE LIGHTING

TYPE A T8

Type A T8 Tube

Make the switch to T8 Type A LED lamps for an effortless upgrade from fluorescent tubes to modern, energy-saving LED technology. Designed for plug-and-play compatibility with existing electronic ballasts, this LED tube offers instant brightness, reduced energy consumption, and a long lifespan of up to 50,000 hours. Perfect for offices, schools, hospitals, retail spaces, and warehouses, it provides uniform, flicker-free lighting with excellent color clarity.



PRODUCT FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- Rated Lifetime L70(hrs): >50,000
- 5 year warranty

KEY SPECIFICATIONS

Lamp Base	G13
Size	4.0 ft
Wattage	9 – 13W
Voltage	BF
CCT	3000K or 4000K or 5000K
Lumens	1800 – 2200 lm
CRI	83+
Beam Angle	320°
Lifespan	50,000 hrs
Dimming	No


SPECIFICATIONS

Order#	Model	Size	Wattage	Voltage	CCT	Lumens	CRI	Beam Angle
R41024	WLL-LEDT8BC9/840/HE	4.0 ft	9W	BF	4000K	1800 lm	>83	320°
R41025	WLL-LEDT8BC9/850/HE	4.0 ft	9W	BF	5000K	1800 lm	>83	320°
R41026	WLL-LEDT8BC10/830/HE	4.0 ft	10W	BF	3000K	1700 lm	>83	320°
R41020	WLL-LEDT8BC13/840/HE	4.0 ft	13W	BF	4000K	2200 lm	>83	320°
R41021	WLL-LEDT8BC13/850/HE	4.0 ft	13W	BF	5000K	2200 lm	>83	320°

DLC CERTIFICATION

Order#	Model	Application	DLC Standard	DLC Premium
R41024	WLL-LEDT8BC9/840/HE	Replacement Lamps	S-CFTJBN	–
R41025	WLL-LEDT8BC9/850/HE	Replacement Lamps	S-4Q09C5	–
R41026	WLL-LEDT8BC10/830/HE	Replacement Lamps	PL6PAK85T12W	–
R41020	WLL-LEDT8BC13/840/HE	Replacement Lamps	PLBXEXKFPEMW	–
R41021	WLL-LEDT8BC13/850/HE	Replacement Lamps	PLTP8IYXTS03	–

ACCESSORIES – MOUNTING




RENO-S-SN-U-PBT
Low profile rotary lock
T8 socket

Order#	Model	Description
R39301	RENO-LBH-HPM	Low profile rotary lock T8 socket

DIMENSIONS

4 FT



Full Body Width: 47.2" (1198.9 mm)

Lens Width: 44.7" (1135.4 mm)

Thickness: 1.0" (25.4 mm)

Weight: n/a