



TRITON Series

NSF Sleek Linear Highbay



Date		Project	
Type		Part Number	

ARCHITECTURAL LUMINAIRES BY RENO LIGHTING™

Designed for demanding environments, the TRITON NSF Sleek Linear Highbay offers exceptional protection against high water temperatures and pressure, paired with a smooth housing design for easy wash-down maintenance. Its streamlined construction ensures maximum efficiency and delivers superior lighting performance for large spaces. Purpose-built to withstand harsh conditions, the TRITON is the ideal solution for applications in food processing, heavy manufacturing, cold storage, and laboratories.



Product Features

- NSF /ANSI 2 Certified: Compliant with food protection and sanitation requirements
- IP69K Rated: Ensures complete protection against dust and high-pressure, high-temperature water jets
- NEMA 4X Certified: Ensures the fixture is water-tight and can withstand extreme conditions
- Finish is salt-spray tested to 1,500 hours per ASTM B117
- Includes: 10ft White Cord, jack chain, and v-hooks
- Durable high impact polycarbonate lens
- Smooth aluminum housing protects the fixture from the accumulation of substances such as food debris and dust
- Designed for environments where equipment must endure rigorous cleaning and sanitation processes
- Sensor-Ready with 3.5mm jack design, compatible with Standalone and RENO Smart Bluetooth Sensors
- Compatible with the RENO All Weather Emergency LED Driver to provide backup power during a power outage
- Operating temp: -40°F to +122°F (-40°C to +50°C)
- Rated lifetime L70: >100,000 hours
- 10 Year Limited Warranty

Key Specifications

Voltage	120-347V
Wattage	Selectable: 100/150/200W
CCT	Selectable: 35/40/5000K
Efficacy	150 lm/W
Lumens	Up to 30,000 lm
CRI	>80
Power Factor	>0.9
THD	<20%
Beam Angle	90°
Dimming	0-10V Dimming
Surge Protection	6kVA
Certifications	NSF/ANSI 2, IP69K, NEMA 4X, ASTM B117, DLC Premium
Mounting	Suspended (Included) or Surface (Additional)
Applications	Food, Pharmaceutical, Automotive, Agricultural, Marinas, Heavy Industrial





TRITON Series | NSF Sleek Linear Highbay

ARCHITECTURAL LUMINAIRES BY 


Specifications

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT
R34150	RENO-SLEEK-LHB-DV-MW-MCCT	100W	120-347V	16,066 lm	160 lm/W	3500K
				16,542 lm	165 lm/W	4000K
				16,082 lm	161 lm/W	5000K
		150W	120-347V	22,391 lm	149 lm/W	3500K
				23,201 lm	154 lm/W	4000K
				22,082 lm	147 lm/W	5000K
		200W	120-347V	30,400 lm	152 lm/W	3500K
				30,869 lm	154 lm/W	4000K
				28,792 lm	144 lm/W	5000K

DLC Information

Order#	Model	Application	DLC Standard	DLC Premium
R34150	RENO-SLEEK-LHB-DV-MW-MCCT	High-Bay Luminaires for Commercial and Industrial Buildings	–	S-7RZ5D4

Accessories



R39121

RENO-SLEEK-LHB-WMK
Surface mount bracket

Order#	Model	Description
R39121	RENO-SLEEK-LHB-WMK	Surface Mount Bracket






TRITON Series | NSF Sleek Linear Highbay

ARCHITECTURAL LUMINAIRES BY  RENO LIGHTING

Accessories - Standalone Sensor & Remotes



R71002
RENO-SENSOR-MW-H
Microwave Sensor



R74004
RENO-SENSOR-PIR3.5-PH15M
Long Detection Range PIR Sensor



R73002
RENO-REMOTE-H
Remote Control for Standalone Sensors (With Screen)



R73005
RENO-REMOTE-H-ECO
Remote Control for Standalone Sensors (Without Screen)

Order#	Model	Description
R71002	RENO-SENSOR-MW-H	Bi-level Microwave Sensor
R74004	RENO-SENSOR-PIR3.5-PH15M	Long Detection Range PIR Sensor
R73002	RENO-REMOTE-H	Remote Control for Standalone Sensors (With Screen) Note: Only 1 needed per project
R73005	RENO-REMOTE-H-ECO	Remote Control for Standalone Sensors (Without Screen) Note: Only 1 needed per project


Accessories - Reno Smart NLC Sensors




R75001
RENO-RS-JK-BPDN-12V
Bluetooth 3.5mm Jack PIR Sensor



R75002
RENO-RS-JK-BMWM-12V
Bluetooth 3.5mm Jack Microwave Sensor



R75201
RENO-RS-GW-BCNW
Bluetooth Ceiling mounted gateway




R75301
RENO-RS-GW-BCNW
Bluetooth Reset remote controller

Order#	Model	Description
R75001	RENO-RS-JK-BPDN-12V	Bluetooth 3.5mm Jack PIR Sensor for RENO Smart NLC System
R75002	RENO-RS-JK-BMWM-12V	Bluetooth 3.5mm Jack Microwave Sensor for RENO Smart NLC System
R75201	RENO-RS-GW-BCNW	Bluetooth Ceiling mounted gateway for RENO Smart NLC System
R75301	RENO-RS-RC-BNNN	Bluetooth Reset remote controller (5-keys)


****All Reno Smart Sensors are programmed/commissioned using our Reno Smart App**



Photometrics - 100W/4000K



Photometrics - 150W/4000K






TRITON Series | NSF Sleek Linear Highbay

ARCHITECTURAL LUMINAIRES BY RENO LIGHTING

Photometrics - 200W/4000K



Dimensions

