

Date		Project	
Type		Part Number	



ALL-IN-ONE PERFORMANCE LIGHTING

SOL Series

Round Slim Surface Fixture

The SOL series Slim Surface Round is one of the most popular fixtures sought after in the commercial property market: a modern, round flush mount fixture that replaces 2 or 3-lamp incandescent ceiling fixtures. This 1" low profile fixture is easy to install and gives a clean, finished look to any room.



PRODUCT FEATURES

- Energystar Certified for 5", 7", and 9"
- Edge-lit technology, no glare or dark spots, instant-on
- This 1" thick luminaire is easy to install on standard J-boxes with a quick snap
- Die-cast aluminum with white translucent acrylic lens
- 12", 15", 19" Avail in Brushed Nickel Trim
- IC-rated and Air-Tight ready and may be in direct contact with insulation
- Suitable for Damp Locations
- Flicker-free 120V forward-phase triac dimming down to 10%
- Operating temperature: -4°F to +104°F (-20°C to +40°C)
- Rated Lifespan: L70 ~50,000 hrs
- 5 year warranty

KEY SPECIFICATIONS

Voltage	120V
Sizes	5", 7", 9", 12", 15" & 19"
Wattage	10W, 15W, 18W, 22W, 30W, 35W
Lumens	Up to 2,200 lm
CCT	27/30/35/40/5000K
Power Factor	>0.9
CRI	>90
Beam Angle	120°
Dimming	120V forward-phase TRIAC Dimming
Mounting	Surface
Applications	Commercial, Residential, Retail Facilities

SPECIFICATIONS - 5" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31101	RENO-S5R-MCCT-WH	10W	120V	600 lm	60 lm/W	2700/3000 3500/ 4000/5000K	White

SPECIFICATIONS - 7" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31102	RENO-S7R-MCCT-WH	15W	120V	900 lm	60 lm/W	2700/3000 3500/ 4000/5000K	White

SPECIFICATIONS - 9" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31103	RENO-S9R-MCCT-WH	18W	120V	1,150 lm	64 lm/W	2700/3000 3500/ 4000/5000K	White

SPECIFICATIONS - 12" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31104	RENO-S12R-MCCT-WH	22W	120V	1,450 lm	66 lm/W	2700/3000 3500/ 4000/5000K	White
R31124	RENO-S12R-MCCT-WH	22W	120V	1,450 lm	66 lm/W	2700/3000 3500/ 4000/5000K	Brushed Nickel

SPECIFICATIONS - 15" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31105	RENO-S15R-MCCT-WH	30W	120V	2,000 lm	67 lm/W	2700/3000 3500/ 4000/5000K	White
R31125	RENO-S15R-MCCT-BN	30W	120V	2,000 lm	67 lm/W	2700/3000 3500/ 4000/5000K	Brushed Nickel

SPECIFICATIONS - 19" SLIM SURFACE

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT	Finish
R31106	RENO-S19R-MCCT-WH	35W	120V	2,200 lm	63 lm/W	2700/3000 3500/ 4000/5000K	White
R31126	RENO-S19R-MCCT-BN	35W	120V	2,200 lm	63 lm/W	2700/3000 3500/ 4000/5000K	Brushed Nickel

ACCESSORIES – TRIM



R31151
RENO-S5RT-BK
5" Black Round Trim



R31152
RENO-S5RT-BN
5" Brushed Nickel Round Trim



R31153
RENO-S7RT-BK
7" Black Round Trim



R31154
RENO-S7RT-BN
7" Brushed Nickel Round Trim



R31155
RENO-S9RT-BK
9" Black Round Trim



R31156
RENO-S9RT-BN
9" Brushed Nickel Round Trim



R31157
RENO-S12RT-BK
12" Black Round Trim




R31158
RENO-S12RT-BN
12" Brushed Nickel Round Trim

Order#	Model	Description
R31151	RENO-S5RT-BK	Black Trim for 5" Slim Surface Fixture
R31152	RENO-S5RT-BN	Brushed Nickel Trim for 5" Slim Surface Fixture
R31153	RENO-S7RT-BK	Black Trim for 7" Slim Surface Fixture
R31154	RENO-S7RT-BN	Brushed Nickel Trim for 7" Slim Surface Fixture
R31155	RENO-S9RT-BK	Black Trim for 9" Slim Surface Fixture
R31156	RENO-S9RT-BN	Brushed Nickel Trim for 9" Slim Surface Fixture
R31157	RENO-S12RT-BK	Black Trim for 12" Slim Surface Fixture
R31158	RENO-S12RT-BN	Brushed Nickel Trim for 12" Slim Surface Fixture

ACCESSORIES – MOUNTING



R31159
RENO-RC4
4" Recessed Can Retrofit Kit




R31160
RENO-RC6
6" Recessed Can Retrofit Kit

Order#	Model	Description
R31159	RENO-RC4	4" Recessed Can Retrofit (E26 ADAPTOR + MOUNTING BRACKET, components for New Construction & Remodeling)
R31160	RENO-RC6	6" Recessed Can Retrofit (E26 ADAPTOR + MOUNTING BRACKET, components for New Construction & Remodeling)


DIMENSIONS

5"




Diameter: $\varnothing 5.39"$ (137 mm)
 Height: 0.63" (16 mm)
 Weight: .55 lbs (0.25 kg)

7"




Diameter: $\varnothing 7.91"$ (201 mm)
 Height: 0.63" (16 mm)
 Weight: .75 lbs (0.34 kg)

9"




Diameter: $\varnothing 9"$ (228 mm)
 Height: 0.63" (16 mm)
 Weight: 1 lbs (0.45 kg)

12"




Diameter: $\varnothing 12"$ (306 mm)
 Height: 0.63" (16 mm)
 Weight: 2.2 lbs (0.99 kg)

15"



Diameter: $\varnothing 15"$ (381 mm)
 Height: 0.63" (16 mm)
 Weight: 3.3 lbs (1.49 kg)

19"



Diameter: $\varnothing 19"$ (483 mm)
 Height: 0.63" (16 mm)
 Weight: 6.5 lbs (2.95 kg)