



# OPS Series

## Architectural Slim Full Cut-Off Wall Pack



Date		Project	
Type		Part Number	

ARCHITECTURAL LUMINAIRES BY  RENO LIGHTING

RENO LIGHTING's OPS series LED Architectural Slim Full Cut-off Wall Pack uses industry-leading LED chips and drivers to deliver a quality, energy saving lighting solution. It is also designed for an easy install, directly fitting onto existing electrical boxes, making it the contractor's choice when replacing older high pressure sodium and metal halide wall packs.



### Product Features

- DLC Premium
- Aluminum Alloy body
- Power coated black (custom colours available)
- Polycarbonate Lens
- Even Light Dispersion and Reduced Glare
- Optional DC Photocell available
- Surge Protection: 4KV (25/40/60W) / 6KV (75/100/120W)
- Operating temperature: -49°F to +113°F (-45°C to +45°C)
- Rated Lifetime L70 >100,000 hrs
- 10 year limited warranty

### Key Specifications

<b>Voltage</b>	120-347V
<b>Wattage</b>	Selectable Wattage: R1 - 25/40/60W R2 - 75/100/120W
<b>Efficacy</b>	125 lm/W
<b>CCT</b>	Selectable: 3000K/4000K/5000K
<b>CRI</b>	>80
<b>Lumens</b>	Up to 15,000 lm
<b>Beam Angle</b>	95°
<b>Dimming</b>	0-10V
<b>Mounting</b>	Wall
<b>Application</b>	Commercial, Parking, School and Hospital





## OPS Series | Architectural Slim Wall Pack

ARCHITECTURAL LUMINAIRES BY  RENO<sup>®</sup> LIGHTING

### Specifications

Order#	Model	Wattage	Voltage	Efficacy	Lumens	CCT
R51027	RENO-SFWP-DV-MCCT-R1	25/40/60W	120-347V	125 lm/W	3,125/5,000/7,500 lm	30/40/5000K
R51028	RENO-SFWP-DV-MCCT-R2	75/100/120W	120-347V	125 lm/W	9,375/12,500/15,000 lm	30/40/5000K

### DLC Certification

Order#	Model	Application	Standard	Premium
R51027	RENO-SFWP-DV-MCCT-R1	Outdoor Full-Cutoff Wall-Mounted Area Luminaires	–	S-P2ZS41
R51028	RENO-SFWP-DV-MCCT-R2	Outdoor Full-Cutoff Wall-Mounted Area Luminaires	–	S-HJVMWT

### Sensor Accessories



RENO-WP-PS  
Standalone Photocell  
Sensor (DC)

Order#	Model	Description
R59101	RENO-WP-PS	Standalone DC Photocell Sensor

### Dimensions

